



Accoat Guide Wire – Seldinger



Dimensions

- Ø 0.018" / 0.46 mm
- Ø 0.021" / 0.54 mm
- Ø 0.025" / 0.64 mm
- Ø 0.028" / 0.72 mm
- Ø 0.032" / 0.82 mm
- Ø 0.035" / 0.89 mm
- Ø 0.038" / 0.97 mm

Length

20 – 450 cm

Surface

Stainless steel
PTFE coated

Distal tip form

Straight tip
J-tip radius: 1,5 – 3 – 6 – 15 mm

Distal flexible length

Standard 4,5 cm flexible tip

Shaft stiffness

Standard
Stiff
Extra stiff
Super stiff
(Extra stiff & Super stiff not available
in dim: 0.018"; 0.021"; 0.025")

Markers

Uncoated stainless steel
OEM
Length 30-150 cm
1 mm wide surface markers
10 cm step

Customised products on request

Description of item code

(H/X/X)-S/Jr-(C)-0xx-L
(example: J3-C-035-150)

H	Stiff guide wire
H-X	Extra Stiff guide wire
H-X-X	Super Stiff guide wire
S	Straight tip
Jr	J-tip radius J1.5 mm J3 mm J6 mm J15 mm
C	PTFE coated
Without C	Stainless steel
M	Surface marker
0xx	Diameter of the guide wire 018: 0.018" (0.46 mm) 021: 0.021" (0.54 mm) 025: 0.025" (0.64 mm) 028: 0.028" (0.72 mm) 032: 0.032" (0.82 mm) 035: 0.035" (0.89 mm) 038: 0.038" (0.97 mm)
L	Length of the guide wire ■ 20 – 450 cm